



Accessories for Rotary Sensors - Shaft couplings






Shaft coupling for 6 up to 10 mm sl	haft diameters, backla	sh-free, double ca	rdanic
Material	Aluminum, PEEK		
Max. torque	1 Nm		
Operating temperature	-40 +16	0° C	
Max. displacements	radial 0.1	mm, angular 0.45	0
Mounting	2 threaded pins with internal hexagon		
Туре	ØA	ØB	P/N
Z-106-G6	6	6	103910
Z-106-G-6,35	6	6,35	103912
Z-106-G10	6	10	103913






Material	stainless s	teel, ground drivi	ng pin
Mounting		1 fillister head screw M2 each with internal hexagon. Angle screwdriver SW 1.5 in delivery included.	
Туре	ØA	ØB	P/N
Z-103-G-3	3	3	005687





Fork coupling for 6 mm shaft diameters, low backlash			
Material	stainless st	eel, ground drivi	ng pin
Mounting		2 fillister head screws M3 each with internal hexagon Angle screwdriver SW 1.5 in delivery included.	
Туре	ØA	ØB	P/N
Z-104-G-6	6	6	005690





Fork coupling for 6 mm shaft diameters, backlash-free		
Material	anodized aluminum, black, driving pin and spring hardened	
Max. transferable torque	5 Ncm	
Mounting	1 fillister head screw M3 each with intenal hexagon	
	Angle screwdriver SW 2.5 in delivery included.	
Туре	P/N	
Z-105-G-6	005691	



Siedle Group

Novotechnik U.S., Inc.

155 Northboro Road Southborough, MA 01772 Phone: 508-485-2244

Fax: 508-485-2430


Email: info@novotechnik.com

© 12/2011

Art.-Nr.: 062 756.1 Subject to changes

© 06/2015 Subject to changes.





anodized aluminum, black	
Spring phosphor bronze	
24 Ncm	
2 threaded pins with internal hexagon	
P/N	
005692	